

GRIPPIN 2004-07 F150 Door Handle Installation Instructions

BILLET
FROM CLEAN TO EXTREME... WE GOT YOU HANDLED

Before starting roll all the windows up



1) Pry up switch panel and unclip



2) remove 10 mm bolt



3) remove speaker panel (clip)



4) Remove 4ea 7/32 speaker bolts



5) remove lower speaker seal



6) pull straight out to remove lower nylon speaker nut inserts



7) Remove inside latch cover panel



8) remove 2ea 8 mm bolts



9) remove 2ea 6 mm on bottom of door



10) Lift off door panel & unclip latch. Set door panel aside



11) remove 2 plugs at rear of door



12) remove 2ea 10 mm bolts at rear of door handle



13) Remove 2 10 mm nuts on the front inside of the door handle



14) release the latch rod at the base with the quick (dis)connector



15) The drivers door also has a lock cylinder quick (dis)connector to release

GRIPPIN

BILLET

FROM CLEAN TO EXTREME... WE GOT YOU HANDLED



16) Remove the front pin with pressure as shown above



17) release the latch by gently prying on the outer (thinner) edge be careful not to break the plastic



18) remove latch and handle



19) remove the rubber pad from the original handle and install on the Grippin Billet Handle

20) reassemble in reverse order from above instructions

Rear Door handle Installation uses the same instruction as above except:

Omit steps 3, 4, 5 & 6

Add steps 4a and 5b shown below



4a) on the rear door, unclip the trim panel



5a) remove 6 mm bolt at the top rear of the door panel and go to step 7 above

Grippin Billet 4323 N Selland #103 Ave, Fresno CA 93722
www.grippinbillet.com Ph 559-360-4577 Fax 559-222-7580