

VSX12

12,000 LB Capacity
(5443 kg)
PN: 76-72151




VSX9.5

9,500 LB Capacity
(4309 kg)
PN: 76-72146



- **PROVEN WINCH DESIGN**
- **INNOVATIVE SOLID STATE ELECTRONICS**
- **VARIABLE SPEED LINE CONTROL**

By outfitting one of the most successful platforms in the lineup with the revolutionary MiFi Technology control system, Mile Marker is able to fuse innovation with proven performance. The VSX 9.5 (9,500 Pound) and VSX 12 (12,000 Pound) winches offer a hi-tech, feature packed addition to one of the industries favorite winch lines. 

PRODUCT FEATURES:

- Variable Speed Controls
- Solid State Electronics
- Powerful Series Wound Motors
- FRP Sheathing on Power Cables
- Rugged Planetary Gear Sets
- Illuminated Controls
- Diagnostic Feedback
- Automatic Load holding Brake
- Galvanized Roller Fairlead
- 100 Feet Galvanized Aircraft Cable



Variable Speed Remote Control

VSX 12 PRODUCT SPECIFICATIONS:

Part Number	76-72151
Rated line pull	12000 lbs (5443 kg)
Gear Train	3 Stage Planetary
Gear Ratio	296:1
Motor	Series Wound, 4.8 hp (3.6 kW), 12 / 24 V
Control Pendant	6 pt
Dimensions (LxWxH)	22.25" X 6.25" X 8.00" (565.2 mm X 158.8 mm X 203.2 mm)
Cable	3/8" X 100' (nominal 14,400 lbs, 6531 kg) (9.53 mm X 30.5 m)
Drum Size:	2.5" X 9" (63.5 mm X 228.6 mm)
Net weight	92 lbs (42 Kgs)
Bolt Pattern	4 Bolt Pattern, 4.5" X 10", (114.3 mm X 254 mm)

VSX 9.5 PRODUCT SPECIFICATIONS:

Part Number	76-72146
Rated line pull	9500 lbs (4309 kg)
Gear Train	3 Stage Planetary
Gear Ratio	212:1
Motor	Series Wound, 4.6 hp (3.4 kW), 12 / 24 V
Control Pendant	Infinite Speed Joystick Remote, 12' (3.7 m)
Dimensions (LxWxH)	22.25" X 6.25" X 8.00" (565.2 mm X 158.8 mm X 203.2 mm)
Cable	3/8" X 100' (nominal 14,400 lbs, 6531 kg) (9.53 mm X 30.5 m)
Drum Size:	2.5" X 9" (63.5 mm X 228.6 mm)
Net weight	92 lbs (42 kg)
Bolt Pattern	4 Bolt Pattern, 4.5" X 10", (114.3 mm X 254 mm)

VSX 12 PERFORMANCE:

LINE PULL		LINE SPEED		MOTOR CURRENT	
lbs.	kgs.	fpm	mpm	amps @ 12 V	
0	0	23	7	90	
2000	907	12.8	3.9	145	
4000	1814	9.7	3.0	185	
6000	2722	7.9	2.4	230	
8000	3629	7.1	2.2	270	
10000	4536	5.1	1.6	315	
12000	5443	4.5	1.4	370	

VSX 9.5 PERFORMANCE:

LINE PULL		LINE SPEED		MOTOR CURRENT	
lbs.	kgs.	fpm	mpm	amps @ 12 V	
0	0	25.7	7.8	85	
2000	907	15.1	4.6	150	
4000	1814	10.5	3.2	210	
6000	2722	7.9	2.4	270	
8000	3629	5.9	1.8	320	
9500	4309	4.3	1.3	375	

